


Paddington II/G™ OPERATING INSTRUCTIONS

Jog your paper well before padding it. Use a padding compound that pours like paint not like molasses. A heavy thick coat does not make it stronger; it just increases the drying time.


1. Loosen the knobs on the back of the backboard and adjust the paper guides to the size paper you will be padding.




2. Be sure the slide table is tight against the backboard. Place your paper between the paper guides and firmly against the backboard.




3. Place the pressure bar on top of the paper with the center notch in-line with the centerline on the backboard. The paper guides should fit between the notches on the pressure bar. If the paper you are padding is not a standard size, you can use just one of the paper guides to stack your paper against, or slide both paper guides out of the way and stack your paper in the center.




4. Be sure the latches are open. Take the rope ends and lay them in the cleats on the pressure bar. Take all of the slack out of the ropes but **do not pull tight enough to extend the springs.**



5. Close the latches. The latches should now be locked with the springs extended about 1/4". This will provide 30 lbs. of pressure on the paper.



6. Pull the slide table towards you until it stops.



7. Remove the backboard and rotate the Paddington II/G™ so the edge to be padded is accessible.



8. Apply the padding compound or carbonless solution to the paper. Be sure to thoroughly brush it on **but not in a thick heavy layer.**



9. Replace the backboard and press the *5-minute* button on the timer at the front of the Paddington II/G™. Be sure the slide table is still pulled forward to the stop and that you can feel the flow of warm air coming up past the paper.



10. When the compound is dry, open both latches at once. To release the ropes, put one hand on the pressure bar, and with your other hand grab the end of the rope and pull toward the center and up at the same time. Repeat the process for the rope on the other side. You can now take the pressure bar off and remove the paper.

Tip #1: Place a piece of card-stock over the backboard slot to catch any compound that might drip.

Tip #2: Using a strip of painter's tape to cover the aluminum angle at the rear of the slide table makes clean up much easier. Painter's tape comes off easier than standard masking tape.

Warranty Statement

Product Satisfaction Guarantee:

Nitney Corporation offers a 60-day satisfaction guarantee. If for any reason you are not satisfied with your purchase, you may return it in the original packaging, in good condition within 60 days from shipping date, for a full purchase price refund.

Extent of Limited Warranty:

Nitney Corporation warrants to the end-user customer that all Paddington II/G™ parts will be free from performance defects for a period of one year from original shipping date. Nitney Corporation's limited warranty covers only those defects that arise as a result of normal use of the product, and does not cover any other problems, including those that arise as a result of improper maintenance, modification or misuse.

In the event of a part defect within the one-year warranty, Nitney Corporation will remedy the defect, without charge to the customer. To obtain performance by Nitney Corporation of its obligation under this warranty the customer must return the defective product, carefully packed in its original carton or other suitable carton to avoid damage in shipping; freight prepaid to Nitney Corporation. Or, Nitney Corporation will provide to the customer the replacement part at no cost for the customer's self installation. Nitney Corporation reserves the right to require any failed part to be returned to Nitney Corporation for inspection as to cause of failure. If the failed part is not returned to Nitney Corporation when required, the customer will be responsible for the costs of the replacement part.

Limitation of Warranty:

TO THE EXTENT ALLOWED BY LOCAL LAW, NEITHER NITNEY CORPORATION NOR ITS THIRD PARTY SUPPLIERS MAKES ANY OTHER WARRANTY OR CONDITION OF ANY KIND, WHETHER EXPRESS OR IMPLIED OR CONDITIONS OF MERCHANTABILITY, SATISFACTORY QUALITY, AND FITNESS FOR A PARTICULAR PURPOSE.

Limitation of Liability:

THE REMEDIES PROVIDED IN THIS WARRANTY STATEMENT ARE THE CUSTOMER'S SOLE AND EXCLUSIVE REMEDIES. IN NO EVENT SHALL NITNEY CORPORATION OR ITS THIRD PARTY SUPPLIERS BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER BASED ON CONTRACT, TORT, OR ANY OTHER LEGAL THEORY AND WHETHER ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.



Paddington II/G™

manufactured and patented
in the USA

Nitney Corporation

12861 Amethyst Street
Garden Grove, CA 92845
(714)896-8625 ♦ FAX: (714)896-8721
www.padit.com